



# LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner

December 2012

## PRODUCT DESCRIPTION

LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner provides the following product characteristics:

<b>Technology</b>	Solvent cleaner
<b>Chemical Type</b>	Solvent blend
<b>Appearance</b>	Water white <sup>LMS</sup>
<b>Viscosity</b>	Very low
<b>Cure</b>	Not applicable
<b>Application</b>	Cleaning of electrical / electronics devices

LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner is a fast evaporating cleaner that leaves no residue. The product is suited for cleaning electrical and electronic devices. It is designed to be an alternative to CFC-113 and 1,1,1-trichloroethane solvents.

The product is used as an electrical contact cleaner to remove grease, dirt, oil, flux and other surface contaminants from sensitive electrical/electronics devices. LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner can also be used to clean motorized instruments, control panels, electrically driven equipment, motors and other electronic devices requiring non-flammable, low residue degreasing agents.

## TYPICAL PROPERTIES OF UNCURED MATERIAL

Specific Gravity @ 25 °C	0.68
Kauri-Butanol Value (KB) , ASTM D 1133-61	40
Surface Tension, ASTM D 1590, dynes/cm	17
Drying Time @ 20 °C, seconds	<30

Flash Point - See MSDS

## Electrical Properties:

Dielectric Breakdown Voltage, ASTM D 877, kV	43
Volume Resistivity, ASTM D 1169, mΩcm	1.3×10 <sup>12</sup>
Total Ionic Conductivity, ASTM D 4308, μmho/cm	<1

## Material Compatibility

LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner is compatible with most metals, many plastics and elastomers. The following table shows the effects of the product on samples, which were Immersed for 30 minutes @ 20 °C. After removing from the solvent, each specimen was wiped dry and allowed to stand for 30 minutes prior to testing. Since plastics and elastomers can be formulated and manufactured to have a wide range of physical properties, it is recommended that compatibility for the particular grade or product formulation be established prior to production cleaning. The following table shows the effects of the product on various plastics and elastomers.

## Material Incompatibility

LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner may be incompatible with some powdered or finely divided/abraded aluminum. It is recommended that the compatibility be established prior to production cleaning.

## LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner Compatibility with Plastics and Elastomers (Tested per ASTM D 543-87)

Plastics / Elastomers	Ranking	Appearance
ABS	2	Dulled Shine
Buna-N	1	No change
Butyl rubber	0	No change
Delrin	0	No change
G-10 Epoxy	0	No change
Neoprene	1	No change
Nylon 101	0	No change
Phenolic	0	No change
Acrylic (PMMA)	2	Line Webbing
Polycarbonate	2	Cloudy
Polyethylene (HD)	0	No change
Polyethylene (LD)	0	No change
Polypropylene	0	No change
PVC	1	No change
Polyetherimide	0	No change
Polybutyleneterephthalate	0	No change

## Ranking Key

0	No visible effect: no significant weight or dimension change
1	Moderate effect on weight and dimension; no visible effect on substrate
2	Not compatible

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected with a sealant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).**

## Directions for use:

1. Hold can 15 to 20 cm (6 to 8 in) from surface to be cleaned.
2. Spray surfaces liberally. Extension tube can be used to pinpoint application.
3. Allow LOCTITE<sup>®</sup> Electronic Contact and Parts Cleaner to fully evaporate from parts prior to bonding to avoid solvent entrapment within the bond joint.



**Loctite Material Specification<sup>LMS</sup>**

LMS dated January 7, 2002. Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

**Storage**

The product is classified as flammable and must be stored in an appropriate manner in compliance with relevant regulations. Do not store near oxidizing agents or combustible materials. Store product in the unopened container in a dry location. Storage information may also be indicated on the product container labelling.

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.** Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

**Conversions**

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$   
 $\text{kV/mm} \times 25.4 = \text{V/mil}$   
 $\text{mm} / 25.4 = \text{inches}$   
 $\mu\text{m} / 25.4 = \text{mil}$   
 $\text{N} \times 0.225 = \text{lb}$   
 $\text{N/mm} \times 5.71 = \text{lb/in}$   
 $\text{N/mm}^2 \times 145 = \text{psi}$   
 $\text{MPa} \times 145 = \text{psi}$   
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$   
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$   
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$   
 $\text{mPa}\cdot\text{s} = \text{cP}$

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada, Inc. the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0