



# MATERIAL SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** LOCTITE HIGH TEMPERATURE FLANGE SEALANT

**Proper Shipping Name:** None allocated.

**Use:** Anaerobic sealant.

**Product Code(s):** 1436426

**Part Number(s):** 38364 (50 ml)

**Supplier:** HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996  
ADHESIVE TECHNOLOGIES  
135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel: (03) 9724 6444  
24 HOUR EMERGENCY CONTACT NUMBER Tel: (03) 9724 6556

## SECTION 2. HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of Safe Work Australia. This material has been classified as Harmful (Xn) and Irritant (Xi).

### Risk phrase(s):

R22 Harmful if swallowed.  
R37/38 Irritating to respiratory system and skin.  
R41 Risk of serious eye damage.  
R43 - May cause sensitisation by skin contact.

### Safety phrase(s):

S24/25 - Avoid contact with skin and eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S28 - After contact with skin, wash immediately with plenty of soap suds.  
S37/39 - Wear suitable gloves and eye/face protection.  
S46 - If swallowed, seek medical advice immediately and show this container or label.

### DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

**SUSDP POISON SCHEDULE:** None allocated.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Polyurethane methacrylate resin		> 60% w/w
Aromatic dimethacrylate ester	[24448-20-2]	5-10% w/w
Hydroxyalkyl methacrylate	[868-77-9]	5-10% w/w
Cumene hydroperoxide	[80-15-9]	1-<3%
Acrylic acid	[79-10-7]	1-<5%
Ethylene glycol	[107-21-1]	< 1% w/w
1-Acetyl-2-phenylhydrazine	[114-83-0]	< 1% w/w

**DATE OF ISSUE:** 21.04.10  
Page 1 of 4

**REVISION OF:** -  
**PRODUCT NAME:** LOCTITE HIGH TEMPERATURE FLANGE SEALANT

**IDH NO:** -



# MATERIAL SAFETY DATA SHEET

## SECTION 4. FIRST AID MEASURES

- Ingestion:** If swallowed, **do not** induce vomiting. For advice, contact a Poisons Information Centre (Phone 13 11 26) or a doctor.
- Skin:** Remove contaminated clothing and wash affected areas with plenty of water. If irritation, redness or blistering occurs, seek medical attention.
- Eyes:** Hold eyes open and flush with water for at least 15 minutes. If irritation develops, seek medical attention.
- Inhalation:** If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.
- Advice to doctor:** Treat symptomatically.
- First Aid facilities:** Eye wash and normal washroom facilities. A safety shower is recommended.

## SECTION 5. FIRE FIGHTING MEASURES

- Suitable extinguishing media:** Use foam, dry chemical or carbon dioxide.
- Hazards from combustion products:** Under fire conditions, it may release carbon monoxide and noxious fumes.
- Precautions for fire fighters and special protective equipment:** If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear protective gloves, chemical goggles and safety boots. For small spills, wipe up with paper towel and place in container for disposal. For large spills contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite) and transfer to sealable containers suitable for storing spilled material. Flush areas in contact with spilled material with adequate warm soapy water to render the area safe for human contact. Note: Residues are not water soluble. Wash down waters may still contain residues which should be collected for disposal. Do not contaminate watercourse. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

## SECTION 7. HANDLING AND STORAGE

- Safe Handling:** Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Avoid breathing vapour.
- Storage:** Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers away from heat, sparks and open flames. Store at or below 38°C.

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- National exposure standards:**
- |                          | TWA:                          |
|--------------------------|-------------------------------|
| Acrylic acid             | 5.9 mg/m <sup>3</sup> (2 ppm) |
| Ethylene glycol (vapour) | 60 mg/m <sup>3</sup>          |
- Engineering controls:** None required under normal conditions of use, but if vapour or mist is being generated, use a local mechanical exhaust system.



## MATERIAL SAFETY DATA SHEET

**Personal protective equipment:** Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, neoprene or butyl rubber gloves and safety glasses with side shields. Use in a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical data:**

Appearance: Blue gel  
Specific gravity: 1.1 @ 26.6°C  
Solubility: Slightly soluble in water  
Flash point (PMCC): > 90°C  
VOC content: 17.2 g/l

### SECTION 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions of temperature and pressure.

**Conditions to avoid:** Open flames, sparks, strong heat.

**Incompatible materials:** This product will be destabilised by strong oxidising agents, aldehydes and reducing agents.

**Hazardous decomposition products:** Combustible liquid. In a fire, it can release carbon monoxide and noxious fumes.

**Hazardous reactions:** None if used for intended purpose.

### SECTION 11. TOXICOLOGICAL INFORMATION

**HEALTH EFFECTS:**

**Acute:**

Ingestion: Harmful if swallowed. This product may cause severe gastrointestinal irritation.  
Skin: Irritating to skin. May cause sensitisation by skin contact.  
Eyes: Contact with the eyes can cause severe irritation.  
Inhalation: Inhalation of vapours may cause respiratory irritation.

**Chronic:** Repeated or prolonged skin contact may cause dermatitis.

**Toxicity information:** None available for this product.

### SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil. This product may be harmful to aquatic organisms.

### SECTION 13. DISPOSAL CONSIDERATIONS

Refer to State Land Waste Management Authority. Normally suitable for disposal by incineration in an approved incineration plant. Containers should be emptied prior to disposal at an approved landfill site.



## MATERIAL SAFETY DATA SHEET

### SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

### SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

### SECTION 16. OTHER INFORMATION

#### Abbreviations/acronyms:

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

TWA - Time-weighted average

#### DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.